

ARIA BY CHANNEL VISION™

Outdoor Speakers

The OS610 outdoor speakers offer exceptional sounds for both outdoor and indoor applications. Its soft lines and curved corner design allows these speakers to fit into both traditional and contemporary decors. The OS610 features UV protected white ABS plastic with aluminum grilles and brackets, stainless steel hardware, a 6.5-inch polygraphite woofer with long lasting rubber surround, and a 1-inch fluid cooled soft dome tweeter. The speakers are designed to be mounted either horizontally or vertically with the included bracket and have a wide range of swivel positions with 1 degree locking points. Alternatively, the OS610 can also be mounted using two M6 mounting holes embedded in the enclosure. With a power handling of 150 watts and sensitivity of 87dB, the OS610 delivers high SPL levels both indoor and out. For local volume control, use the VC300 impedance matching volume control.

Features:

- 6.5" injected polypropylene woofer with butyl rubber surround.
- 1" fluid-cooled silk tweeter with 12oz magnet structure
- Frequency response: 55Hz-20kHz +/-3dB
- Recommended amplifier power: 10W to 150W
- Ultraviolet fade protection
- All stainless steel hardware
- Aluminum grilles (2)
- Aluminum brackets (2)



Specifications

Frequency response	55Hz to 20Khz +/- 3dB
Power handling	10W to 150W
Sensitivity	87dB at 1 meter w/ 1 watt
Impedance	8 ohms
Gold plated terminal post	Accepts up to 14AWG wire

Drivers

Woofer (1)	6.5 inch polygraphite
Tweeter (1)	1 inch fabric soft dome
Crossover	2nd order Linkwitz-Reilly 12dB octave
Dimensions	8.5w x 13.5 x 8.75d inches (21.59cm x 34.29cm x 34.29cm) 7.5 Lbs. with bracket

Note: The OS610 is weather resistant, not weatherproof or waterproof. Ideal placement, for longevity is under an eave or protected area.



CHANNEL VISION™

234 FISCHER AVENUE • COSTA MESA, CA 92626
(714) 424-6500 • (800) 840-0288 • (714) 424-6510 fax
www.channelvision.com • email: sales@channelvision.com