



SAM-RF4

1x4 RF splitter, F connector, 1GHz, SCTE compliant



SAM-RF6

1x6 RF splitter, F connector, 1GHz, SCTE compliant



SAM-RF8

1x8 RF splitter, F connector, 1GHz, SCTE compliant

Features

- Industry approved
- F-ports are digital ready, meet ANSI/SCTE 02 2006
- Vertical port orientation simplifies access and cable management

Product Description

Suttle 1GHz video splitter modules provide high quality and reliable video distribution with industry approved, digital ready splitters that meet ANSI/SCTE standards. The angled mounting brackets maximize enclosure space, minimize cable strain, and facilitate better cable management and ease of installation.

Specifications

	SAM-RF4	SAM-RF6	SAM-RF8
Frequency Range	5 - 1000MHz	5 - 1000MHz	5 - 1000MHz
Return Loss	22 - 29dB	17 - 21dB	21 - 30dB
Insertion Loss	7 - 8dB	9 - 11.5dB	10.5 - 11.5dB
Isolation	27 - 36dB	21 - 24dB	21 - 40dB
RFI Shielding	120dB	130dB	120dB
"F" Ports	Digital - Meet ANSI/SCTE 02 2006		
Dimensions	2.75" H x 6.5" W x 2.8" D		

