

3 x 8 HDMI™ Splitter/Extender with IR Remote Control



VIDEO ENRICHMENT PRODUCTS

Allows three HDTV audio/video device (digital cable box, DVD player) with a HDMI output to be connected to up to eight HDTV display devices (HDTV, LCD projector) with HDMI inputs

Ideal for home theater, conferences, conventions, restaurants, school and corporate training and presentations.

Use as an extender by placing at the end of a long HDMI cable to regenerate the HDMI signal

Distributes clean and superior digital audio and video signals to up to 8 HDTV sources with zero signal loss

Supports High Definition Resolutions 1080p, 1080i, 720p, and Standard Video Format

Supports Computer Resolutions UXGA (1600x1200), SXGA (1280x1024), XGA (1024x768), SVGA (800x600), VGA (640x480)

H.D.C.P. (High-Bandwidth Digital Content Protection) Compliant

- Fully HDMI Version 1.2 Compliant

Allows simultaneous display

- Active LED Indicator Light
- Precision Machined Metal Construction
- Installs in Seconds
- Includes an IR Remote Control

SPECIFICATIONS

- 3 Inputs to 8 Outputs
- Audio/Video Input Connector Type: HDMI (19 Pin - Type A) Female
- Audio/Video Output Connector Type: HDMI (19 Pin - Type A) Female
- Video Amplifier Bandwidth: 1.65 Gbps
- Single Link Range: 1080p (1920 x 1200)
- Vertical Frequency Range: 60 Hz
- Power Consumption: 36 Watts, Max
- Input Video Signal: 1.2 Volts p-p
- Input DDC Signal: 5 Volts p-p (TTL)

- Power Supply: 12 Volt DC
- HDMI Output: 5V DC, 500 mA
- Dimensions: 13.7 L x 6.71 W x 1.26 H

Extender Specifications:

- Self Powered Circuitry
- Total Transmitting Range: 1080p/1080i/720p - 100 ft., Total Length
- Status Indicator Light

280338

Pkg.:

Pkgd