

1 x 8 VGA Splitter



VIDEO ENRICHMENT PRODUCTS

Use to duplicate and boost signals from a single source to eight monitors or other display devices

Supports VGA, SVGA, XGA, QXGA, and Multi-Sync Compliant Monitors

Ideal for Commercial Demonstrations, Conferences, Conventions, School and Corporate Training and Presentations

Supports Computer Resolutions UXGA (1600x1200), SXGA (1280x1024), XGA (1024x768), SVGA (800x600), VGA (640x480)

Features a Bandwidth of 450 MHz per Port for Video Input and Output

Precision Machined Metal Construction

Specifications:

- ~~Power Supply~~ 115 VAC, Input
- Able to Daisy-Chain with Multiple Units to Generate More Outputs
- Supports 450 MHz Video Bandwidth for Each Port
- Supports Video Resolutions of Up to 2048 x 1536
- Graphics Standards Compliant: VGA, SVGA, XGA, QXGA, and Multi-Sync
- (1) Input Connector: HD-DB15 (15 Pin) Female Jack
- (8) Output Connectors: HD-DB15 (15 Pin) Female Jacks
- Video Bandwidth: 450 MHz
- Video Resolution: 2048x1536 Max
- Signal Transmission Distance:
 - Supports up to 120 feet with Resolution of 1024x768
 - Supports up to 120 feet with Resolution of 1600x1200
 - Supports up to 100 feet with Resolution of 1920x1440
 - Supports up to 100 feet with Resolution of 2048x1536

Note: Incompatible with CGA, EGA, and Mono Monitors

280448

Pkg.:

Pkgd